



Heil Sound Suggested Accessories



All in and out of warranty items returned must be accompanied by a completed repair form, which can be found at <http://heilsound.com/pro/repairs>
Heil Sound, Ltd. warrants these products to the original purchaser for a period of three years parts and 90 days labor from the date of purchase. It does not cover accidental or intentional damage. Heil Sound, Ltd. is not responsible for loss, damage or expenses that arise from the use or the inability to use this product.

Heil Sound, Ltd.
5800 North Illinois Fairview Heights, IL 62208
618.257.3000 (phone) 618.257.3001 (fax)
info@heilsound.com



www.heilsound.com



THE HERITAGE

The Heritage is modeled after the look of the 1950s era microphones, but with a modern large diaphragm element.
Look cool, but sound great!

The Heritage

Heil Sound has reintroduced the Heritage, a stylish dynamic microphone with a vintage look that is equally at home in live sound, recording, and broadcast applications. The exceptional performance is achieved by the use of a special magnet structure with a large 1 1/4" aluminum low mass voice coil assembly similar to the Heil PR 20. The frequency response is 50 Hz - 18 kHz with a mid range boost at 4 kHz, which results in incredible brilliance and presence. Special attention has been paid to the phasing plug assembly with equally placed ports that sense audio from the back of the microphone entering those sounds out of phase. The result is a tight cardioid pattern with superior rear rejection. The Heritage has a slide switch that turns the audio on and off and has a small lock screw that can lock it in position.

The Heritage comes in two finishes; chrome with blue, and black matte with blue. The chrome finish is a special 'show chrome' where the steel body is copper plated and then double chrome plated producing a deep chrome finish. A molded internal foam windscreen inside the grill covers the Heil dynamic microphone element mounted in a specially tooled rubber shock mount.

Standard 5/8" - 27 microphone stand threads allow The Heritage to be mounted on booms or floor stands.

Output Connection	3 pin XLR
Element Type	Dynamic
Frequency Response	50 Hz - 18 kHz
Polar Pattern	Cardioid
Rear Rejection @ 180° off axis	-30 dB
Impedance	600 ohms balanced
Output Level	-55 dB @ 1 kHz
Weight	24.9 oz.
Max SPL	142 dB

