

Specifications for optional filters

Model	Center frequency	Bandwidth -6 dB	Bandwidth -60 dB	Guaranteed attenuation	Transceivers
YG-455C	455.7 kHz	500 Hz	820 Hz	More than 80 dB	TS-830S/R-2000
YG-455C-1	455.0 kHz	500 Hz	820 Hz	More than 80 dB	TS-950S/940S/930S/850S/140S/680S
YG-455CN	455.7 kHz	250 Hz	500 Hz	More than 80 dB	TS-830S
YG-455CN-1	455.0 kHz	250 Hz	480 Hz	More than 80 dB	TS-930S/940S/950S/850S
YK-455C-1	455.0 kHz	500 Hz	820 Hz	More than 80 dB	TS-140S/680S
YK-455S-1	455.0 kHz	2.4 kHz	4.1 kHz	More than 80 dB	TS-950S
YK-88A	8831.5 kHz	6 kHz	11 kHz	More than 80 dB	TS-430S/670
YK-88A-1	8830.0 kHz	6 kHz	11 kHz	More than 80 dB	TS-930S/940S, R-5000
YK-88C	8830.7 kHz	500 Hz	1.8 kHz	More than 80 dB	TS-130SE·S·V/430S/440S/530S·SP/830S/670, R-5000
YK-88C-1	8830.0 kHz	500 Hz	1.5 kHz	More than 80 dB	TS-930S/940S/950S/850S
YK-88CN	8830.7 kHz	270 Hz	1.2 kHz	More than 80 dB	TS-130SE·S·V/430S/440S/530S·SP/830S/670, R-5000
YK-88CN-1	8830.7 kHz	500 Hz	1.5 kHz	More than 80 dB	TS-950S/850S
YK-88S	8830.0 kHz	2.4 kHz	4.4 kHz	More than 80 dB	TS-440S
YK-88SN	8830.0 kHz	1.8 kHz	3.6 kHz	More than 80 dB	TS-130SE·S·V/430S/440S/530S·SP, R-5000
YK-88SN-1	8830.0 kHz	1.8 kHz	3.6 kHz	More than 80 dB	TS-950S/850S