

# FT-600

## COMPACT HF TRANSCEIVER

# YAESU

*...leading the way.<sup>SM</sup>*

### **Amateur operating simplicity and commercial practicality.**

The FT-600 compact HF base station cinches Yaesu's leadership position in amateur radio manufacturing. Combining the straightforward, sensible layout of a commercial radio with the most-often-used features on the front panel, the FT-600 is comparable to its commercial counterpart, and excels as an easy-to-use base station or mobile radio.

- Frequency Coverage:
  - RX: 50 kHz~30 MHz
  - TX: 160~10m Amateur Bands Only
- Direct Digital Synthesis (DDS)
- 100 Memory Channels (in 4 banks of 25)
- Front Mounted Speaker w/High Audio Output
- Direct Keypad Frequency Entry
- Alphanumeric Display
- Selectable Noise Blanker
- MIL-STD 810 Rating
- Omni-Glow™ Display
- Dual Watch



# Accessories & Options

# Specifications

- FC-800 Automatic Antenna Tuner
- FIF-232C Computer Interface
- FP-800 AC Power Supply
- MD-100A8X Desk Microphone
- SP-7 Mobile Speaker
- SP-8 Base Station Speaker
- TCXO-4 High Stability Reference Oscillator
- YA-007 Mobile Antenna
- YA-30 Broadband Dipole Antenna
- YF-112A 6 kHz AM Filter
- YF-112C 500 Hz CW Filter
- YH-77STA Lightweight Stereo Headphones



## General

Receiving Frequency Range: 50 kHz~30 MHz  
 Transmitting Frequency Range:  
 160 ~ 10 meter Amateur Bands  
 Frequency Stability:  
 ±10ppm from 0 ~ +40°C (Standard Version)  
 ±2ppm from 0 ~ +50°C (w/TCXO-4 option)  
 Emission Modes:  
 USB, LSB (J3E), CW (A1A), AFSK (J2B),  
 AM (A3E)  
 Frequency Tuning Steps:  
 10 Hz/100 Hz (CW,SSB)  
 100 Hz/1 kHz (AM)  
 Antenna Impedance: 50Ω nominal  
 Operating Temperature Range: -10 ~ +50°C  
 Supply Voltage:  
 13.5 V DC ±10%, negative ground  
 Power Consumption (approx.):  
 1.2 A RX (no signal)  
 20 A TX (100 Watts)  
 Dimensions (WHD):  
 244 x 104 x 286 mm (w/o Knobs)  
 (9.6 x 4.1 x 11.3 in.)  
 Weight (approx.): 4.5 kg (9.9 lbs.)

## Transmitter

Power Output: 100 Watts (25W AM Carrier)  
 Modulation Types:  
 SSB: Balanced Modulator, filtered carrier  
 AM: Low-level (early stage)  
 Spurious Radiation:  
 >40 dB below peak output  
 SSB Carrier Suppression:  
 >40 dB below peak output  
 Undesired Sideband Suppression:  
 at least 50 dB  
 below peak output at 1.5 kHz modulation  
 Audio Response (SSB):  
 not more than -6 dB from 400 ~ 2600 Hz  
 3rd order IMD:  
 -25 dB typical @100 Watts PEP 14.2 MHz  
 Microphone Impedance: 500 to 600 Ω

## Receiver

Circuit Type:  
 Double-conversion superheterodyne  
 Intermediate Frequencies:  
 1st 47.055 MHz  
 2nd 8.215 MHz

## Sensitivity (For 10 dB S/N):

Mode (BW)	Frequency	
	0.5~1.8 MHz	1.8~30 MHz
SSB, CW (2.4 kHz)	<2 μV	0.25 μV
AM (6 kHz)	<8 μV	<1 μV

## Selectivity :

Modes	Minimum 6 dB BW	Maximum 60 dB BW
CW narrow (optional)	500 Hz	1.2 kHz
SSB, CW, AM narrow	2.2 kHz	5.0 kHz
AM-wide (optional)	6 kHz	12 kHz

Squelch Sensitivity:  
 1.8~30 MHz (CW, SSB, AM): <2.0 μV  
 IF Rejection (1.8~30 MHz):  
 60 dB or better  
 Image Rejection (1.8~30 MHz):  
 70 dB or better  
 Clarifier Tuning Range: ±300 Hz  
 Maximum Audio Power Output:  
 at least 1.5 Watts into 4Ω with <10% THD  
 Audio Output Impedance: 4 to 8Ω

Specifications may be subject to change without notice or obligation. Specifications guaranteed only within amateur bands.

For the latest Yaesu news, visit us on the Internet: <http://www.vxstd.com>

About this brochure: we have made this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time in equipment, optional accessories, specifications, model numbers, and availability. Precise frequency range may be different in some countries. Some accessories shown herein may not be available in some countries. Some information may have been updated since the time of printing; please check with your Authorized Yaesu Dealer for complete details.

**YAESU** VERTEX STANDARD CO., LTD.  
 4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

**VERTEX STANDARD** Phone 562/404-2700 ; Fax 562/404-1210  
 Email:amateursales@vxstd.com

**US Headquarters**  
 17210 Edwards Road, Cerritos, CA 90703, U.S.A.  
**International Division**  
 8350 N.W. 52nd Terrace, Suite 201, Miami, FL 33166, U.S.A.

**YAESU EUROPE B.V.**  
 P.O. Box 75525, 1118 ZN Schiphol, The Netherlands

**YAESU UK LTD.**  
 Unit 12, Sun Valley Business Park, Winnall Close  
 Winchester, Hampshire, SO23 0LB, U.K. Email:sales@yaesu.co.uk

**YAESU GERMANY GmbH**  
 Am Kronberger Hang 2, D-65824 Schwalbach, Germany

**VERTEX STANDARD HK LTD.**  
 11th Floor Tsim Sha Tsui Centre, 66 Mody Rd.,  
 Tsim Sha Tsui East, Kowloon, Hong Kong