CHASSIS No. 4 – HI LEVEL R F

CHASSIS No. 3 – POWER SUPPLY

CHASSIS No. 4 – LO LEVEL R F

CHASSIS No. 5 – VFO

CHASSIS No. 2 – AF

CHASSIS No. 1 – SSB GENERATOR

RESISTORS ARE 1/2 WATT 10% EXCEPT AS OTHERWISE SPECIFIED

K = X 1,000 M = X 1,000,000

CAPACITOR VALUES SHOWN DECIMALLY ARE MICROFARADS, OTHERS ARE MICROMICRO – FARADS EXCEPT AS OTHERWISE SPECIFIED

	CERAMIC CAPACITOR
▷ = .005 & 20%	•
▷ = 10 % JF OR JL	•
▷ = 20% SM	•
▷ = NPO	•
▷ = +80% –20%	•
▷ = • TA	•
▷ = • 50V	•
▷ = 20% 25U	•
▷ = SILVER MICA	•
▷ = MYLAR	

= • LETTERED LUG

● = TIE POINT LUG

◎ = TEST POINT (COLOR CODED)

SH= SHIELDED AUDIO CABLE

○ = MOUNTED ON RESISTOR BOARD (SEE MANUAL.)

ALL SWITCHES ARE SHOWN AS SEEN FROM REAR. THE NUMBERS DENOTE WAFER POSITION. No. 1 IS NEXT TO PANEL. THE LETTERS R & F DENOTE REAR & FRONT SECTIONS OF WAFER, RESPECTIVELY. THE FRONT SECTION CONTACTS ARE SHOWN BY DASHED LINES & ARE AS VIEWED THRU THE WAFER FROM REAR. THE BLACKED ROTORS ARE ON REAR SECTION. SOME WAFERS HAVE LUGS (WITHOUT CONTACTS) WHICH ARE USED AS TIE POINTS.

THE THREE PLUG-IN COIL UNITS, 2ND MIXER, RF DRIVER & XTAL OSC PLATE SHOW THE CIRCUIT USED ON THE 40 METER BAND. REFER TO CHART (IN INSTRUCTION MANUAL) FOR OTHER BANDS. EACH OF THE ABOVE PLUG-IN COIL UNITS CONTAINS SIX COILS, WHEN AN "X" BAND COIL IS INCLUDED.

PLUG-IN COIL SOCKET-LUG VIEW



CENTER LUGS ARE TIE POINTS & HAVE NO INTERNAL CONNECTIONS.

NUMBERED ARROWS AROUND THE GANGED BAND-SWITCH DESIGNATE WHERE WIRE CONNECTIONS GO TO A PLUG-IN-COIL GROUP ASSOCIATED WITH THE PARTICULAR SWITCH FUNCTION.

LAST R AND C NUMBERS

R166 R287 R311 R490 R513
C145 C249 C307 C499 C514

S & F = START & FINISH, RESPECTIVELY, OF COIL WINDING.

2T = 2 TURNS

✳ DC RESISTANCE OF P.T. SECONDARY HI VOLTAGE WINDING.
21 Ω BETWEEN R-Y & BL
5 Ω " R-Y & R-GN
42 Ω " R-Y & R

R 488	REMOVED
C 241B	ADDED
C 429	WAS 5 MMFD
C 419	WAS .005
C 481	WAS EACH 68K
C 482	
R 228	WAS 2.2K
R 243	WAS 1K
R 254	WAS 1.5K

REV. 10-6-60	CHKD ←	APPRD GEM
R 433A	WAS 1K	
R 426	" 1.5K	
R 436	" 220Ω	
R 447B	ADDED 250Ω RHEO	
R 445B	" 47K	
R 440A	" 100K POT	
R 435A	" 27K	
R 470A	" 120 Ω	
R 239A	" 18K	
R 127	WAS 8.2K	
R 133	" 4.7K	
C 458A	ADDED	
C 470B	WAS 4 MMFD	
C 433	" .005	
REV. 7-21-60	CHKD ←	APPRD GEM
REV. 4-28-60	CHKD ←	APPRD GEM
REV. 12-7-59	CHKD GEM	APPRD GEM
REV. 11-6-59	CHKD GS	APPRD GEM

SCHEMATIC & WIRING DIAGRAM
RADIO TRANSMITTER

MODEL 100V

CENTRAL ELECTRONICS
CHICAGO

DRG No.	W2201		7-17-59
DRN	A.W.	CHKD	APPVD GEM